

RPM/Rate meters, Totalisers, Power Meters

SAINT WIEN

RPM/Rate/Hz meter



R1-4DO

Programmable digital RPM/Rate/Hz meter.

Digits: 4 digit LED.
 Power supply: 110/220Vac.
 Sensor power: 12Vdc, 60mA.
 Prescaler: 000.001 ~ 999.999.
 Range: 4.0 ~ 3000.
 Input: Solid state, 3k3 Hz max.
 Size: 96 x 48

MODEL	DESCRIPTION	PRICE
R1-4DO	RPM / Rate / Hz Meter.	\$213.00

Totaliser



LC8M

Digital totaliser.

Digits: 8 digit LCD.
 Power supply: Battery - 3 year life.
 Mode: Up count.
 Input: AC Volt / Contact / DC Volt
 Reset: Panel Reset, External reset.
 Size: 31 x 56

MODEL	DESCRIPTION	PRICE
LC8MA	80~250Vac Input 10Hx Max.	\$55.00
LC8MAR	80~250Vac Input 10Hx Max with Panel Reset.	\$61.00
LC8MC	Contact / Switch Input 10Hx Max.	\$55.00
LC8MCR	Contact / Switch Input 10Hx Max with Panel Reset.	\$61.00
LC8MD	6~30Vdc Input 10Hx Max.	\$55.00
LC8MDR	6~30Vdc Input 10Hx Max with Panel Reset.	\$61.00
LC8NC2	Contact / Switch Input 30Hx Max. Size: 24 x 48.	\$55.00

Hours run



LT8M

Digital hours run meter.

Digits: 8 digit LCD.
 Power supply: Battery - 3 year life.
 Range: 9999 hours 59 min.
 Input: AC Volt / Contact on/off DC Volt
 Reset: Panel Reset, External reset.
 Size: 31 x 56

MODEL	DESCRIPTION	PRICE
LT8MA	80~250Vac Input 10Hx Max.	\$55.00
LT8MAR	80~250Vac Input 10Hx Max with Panel Reset.	\$61.00
LT8MC	Contact / Switch on/off Input 10Hx Max.	\$55.00
LT8MCR	Contact / Switch on/off Input 10Hx Max with Panel Reset.	\$61.00
LT8MD	6~30Vdc Input 10Hx Max.	\$55.00
LT8MDR	6~30Vdc Input 10Hx Max with Panel Reset.	\$61.00

Current Meter



PM491AAC

AC Amps Digital Indicator.

Display: 4 digit, 15mm high.
 Programmable.
 Power supply: 110/220Vac.
 Size: 96 x 48

MODEL	DESCRIPTION	PRICE
PM491AAC	0~5 Amps Input - Digital Panel Meter.	\$55.00

Volt Meter



PM491VAC

AC Volts Digital Indicator.

Display: 4 digit, 15mm high.
 0~500Vac
 Power supply: 110/220Vac.
 Size: 96 x 48

MODEL	DESCRIPTION	PRICE
PM491VAC	0~500Vac Input - Digital Panel Meter.	\$55.00

Proximity Sensors

MODEL	DESCRIPTION	PRICE
	Inductive proximity sensor with LED indicator. Power supply: 12~24Vdc. 10mA. Temperature: -20~70°C.	
PLX4P PLX4N	Range: 4 mm. Dimension: 60 x Ø12mm. Output: PNP 100mA. Output: NPN 100mA.	\$45.00 \$45.00
PLX5P	Range: 5 mm. Dimension: 60 x Ø18mm. Output: PNP 100mA.	\$58.00
PLX10P	Range: 10 mm. Dimension: 90 x Ø30mm. Output: PNP 100mA.	\$88.00





MODEL	DESCRIPTION	PRICE
	Inductive proximity sensor with LED indicator. Power supply: 12~24Vdc. 10mA. Temperature: -20~70°C.	
PL4P PL4N	Range: 4 mm. Dimension: 18 x 18 x L35mm. Output: PNP 100mA. Output: NPN 100mA.	\$25.00 \$25.00
PLH5P	Range: 5 mm. Dimension: 18 x 18 x L38mm. Output: PNP 100mA.	\$28.00
PL10P	Range: 10 mm. Dimension: 30 x 30 x L53mm. Output: PNP 100mA.	\$50.00



MODEL	DESCRIPTION	PRICE
	Photo diffusion reflective sensor with LED indicator. Power supply: 12~24Vdc. 30mA. Temperature: -20~70°C.	
RS-V30PN	Range: Adjustable, 100~300 mm. Dimension: 80 x Ø18mm. Output: PNP 100mA.	\$95.00



MODEL	DESCRIPTION	PRICE
	Capacitive proximity sensor with LED indicator. Power supply: 12~24Vdc. 20mA. Temperature: -20~70°C.	
CPLX10P CPLX10N	Range: 30 mm. Dimension: 85 x Ø18mm. Output: PNP 100mA. Output: NPN 100mA.	\$90.00 \$90.00



Counters / Timers

Counter/Timer



CT1-6D2

Programmable digital counter/timer.

Digits: 6 digit LED. 2 presets.
 Power supply: 110/220Vac.
 Output: 2 x Relay SPDT. 3A, 250Vac.
 Sensor power: 12Vdc, 60mA.

Counter.....

Mode: Up count.
 Reset: External, Auto, Manual.
 Pre-scale: 000.000~999.999
 Input: Contact. 30 Hz max.
 Solid state. 6~30Vdc. 3k Hz max.

Timer.....

Mode: On delay.
 Reset: External, Auto, Manual.
 Input: External gate for timer hold.
 Ranges: 4 selectable ranges,
 9999H59M, 9999M59S, 99999.9S, 999.999S

MODEL	SIZE	PRICE
CT1-6D2	96 x 48	\$278.00

Counter/Timer



CT3-4D2

Programmable digital counter/timer.

Digits: 4 digit LED. 2 presets.
 Power supply: 110/220Vac.
 Output: 2 x Relay SPDT. 3A, 250Vac.
 Sensor power: 12Vdc, 20mA.

Counter.....

Mode: Up count.
 Reset: External, Auto, Manual.
 Pre-scale: 000.000~999.999
 Input: Contact. 30 Hz max.
 Solid state. 6~30Vdc. 3k Hz max.

Timer.....

Mode: On delay.
 Reset: External, Auto, Manual.
 Input: External gate for timer hold.
 Ranges: 4 selectable ranges,
 99H59M, 99M59S, 999.9S, 99.99S

MODEL	SIZE	PRICE
CT3-4D2	48 x 48	\$195.00

Counter/Timer



TC49

Programmable digital counter/timer.

Digits: 6 digit LED.
 Power supply: 110/220Vac.
 Sensor power: 12Vdc, 50mA.

Counter.....

Mode: 7 counting versions.
 Reset: External.
 Input: Contact. 30 Hz max.
 Solid state. 3k Hz max.

Timer.....

Mode: Up
 Reset: External.
 Input: Contact.
 8 Ranges: From 99H59M59S to 999.999S

MODEL	SIZE	PRICE
TC49	96 x 48	\$195.00

Counters / Timers

Programmable digital counter.

Digits: 6 digit LED. 1 preset.
 Power supply: 110/220Vac.
 Mode: Up/down/reversible.
 Reset: Panel/remote, Auto/man.
 Input: Contact. 30 Hz max.
 Solid state. 3k Hz max.
 Output: Relay SPDT. 3A, 250Vac.
 Sensor power: 12Vdc 50 mA.

MODEL	SIZE	PRICE
H7N-6DM	72 x 72	\$260.00



H7N-6DM

Counter

Programmable digital counter.

Digits: 5 digit LED. 1 preset.
 Power supply: 220Vac.
 Mode: Up count.
 Reset: Panel, Auto/man.
 Input: Contact. 30 Hz max.
 Solid state. 3k Hz max.
 Output: Relay SPDT. 3A, 250Vac.
 Sensor power: 12Vdc 20 mA.

MODEL	SIZE	PRICE
H7K-52-5U	48 x 48	\$203.00



H7K-52-5U

Counter

Analogue timer.

Power supply: 220Vac.
 Mode: 1 preset. On delay.
 Start/reset: Power on/off.
 Ranges: 4 selectable ranges, 6 sec, 60 sec, 6 min, 60 min.
 Relay rating: 3A, 250Vac.
 Price includes 8 pin base.
 Size: 48 x 48

MODEL	DESCRIPTION	PRICE
H2K1	1 timed SPDT.	\$65.00
H2K2	1 timed DPDT.	\$65.00
H2K3	1 timed SPDT. 1 instant SPDT.	\$65.00



H2K

Timer

Digital timer.

Digits: 5 digit LED. 1 preset.
 Power supply: 220Vac.
 Mode: On delay.
 Start/reset: Power on/off.
 Input: External gate for timer hold.
 Output: Relay SPDT. 3A, 250Vac.
 Ranges: 4 selectable ranges,
 999.99S, 999M59S,
 9H59M59S, 999H59M.

MODEL	SIZE	PRICE
H5K-52-5U	48 x 48	\$203.00



H5K-52-5U

Timer

Programmable digital timer.

Digits: 6 digit LED. 1 preset.
 Power supply: 110/220Vac.
 Timing: Up/down.
 Mode: 8 operation modes.
 Start/reset: Panel/remote, Auto/man.
 Input: External gate for timer hold.
 Output: Relay SPDT. 3A, 250Vac.
 Ranges: 8 selectable ranges, from 99H59M59S to 999.999S.

MODEL	SIZE	PRICE
H5N-6DM	72 x 72	\$240.00



H5N-6DM

Timer